



Длина стрелы	М	10,2 (min)	40,0 (max)
Вылет стрелы (min - max)	М	2,5 ÷ 7,0	7,0 ÷ 36,0
Грузоподъемность (max - min)	Т	55,0 ÷ 26,0	10,1 ÷ 1,5
Высота подъема крюка	М	8,8 ÷ 3,8	39,7 ÷ 12,0
Длина стрелы с max удлинителем (40+16)	М	56,0	
Вылет стрелы	М	9,0	46,0 (48*)
Грузоподъемность	Т	2,8	0,3 (0,4*)
Высота подъема крюка	М	~56,0	30,0 (24*)

* При условиях: Стрела - 40 м + 16,0 м, угол наклона удлинителя - 20°

Вылет, М	Стрела 10,2 м			Стрела 13,6 м		Стрела 17,0 м		Стрела 20,5 м		Стрела 23,9 м		Стрела 27,3 м		Стрела 30,8 м		Стрела 34,2 м		Стрела 37,6 м		Стрела 40,0 м		Вылет, М
	Q*	Q	H	Q	H	Q	H	Q	H	Q	H	Q	H	Q	H	Q	H	Q	H	Q	H	
2,5	55																					2,5
2,7	53																					2,7
3,0	51	49																				3,0
3,5	47	44.5		44.5		42.5																3,5
4,0	43.5	41	8.8	41	12.8	38.5	16.8	36.5	20.3													4,0
4,5	39.5	37.5	8.2	37.5	12.6	35	16.5	33	20.2	31	23.6											4,5
5	37	34.5	7.5	34.5	12.3	33	16.1	31.5	20.0	30.5	23.5	23.3	27.2									5
6	31.5	28.8	6.3	29	11.7	29.1	15.8	27.9	19.8	26.8	23.2	20.9	27.0	18.5	30.2	15.1	34.0					6
7	26	24.1	3.8	24.4	10.7	24.9	15.0	23.2	19.1	22.2	22.8	18.9	26.5	16.9	30.0	14.8	33.6	12.1	37.2	10.1	39.7	7
8				20.9	9.7	21.2	14.2	20.2	18.4	18.9	22.3	17.2	26.0	15.6	29.8	13.9	33.2	11.4	37.0	10	39.4	8
9				17.6	7.9	17.9	13.3	17.4	17.7	16.3	21.8	15.7	25.6	14.3	29.4	13.1	33.5	10.9	36.6	9.5	39.1	9
10				14.9	6.0	15.2	12.3	15.1	17.0	14.3	21.2	13.8	25.2	13	29	12.2	32.8	10.4	36.2	9.1	38.8	10
12						11.4	9.8	11.4	15.2	11.6	19.9	11.4	24.0	10.8	28.0	10.2	31.9	9.5	35.6	8.4	38.1	12
14						9.1	4.9	9.2	13.0	9.3	18.2	9.1	22.6	8.9	26.9	8.6	30.8	8.4	34.6	7.8	37.2	14
16								7.7	9.8	7.6	16.0	7.4	20.9	7.5	25.4	7.5	29.6	7.0	33.6	6.9	36.3	16
18										6.4	13.1	6.5	18.9	6.3	23.9	6.3	28.3	5.9	32.4	5.8	35.2	18
20										5.4	9.0	5.5	16.2	5.4	21.8	5.3	26.6	5.1	31.0	5.0	34.0	20
22												4.7	12.9	4.6	19.5	4.5	24.8	4.2	29.3	4.1	32.4	22
24												4.1	7.1	4.0	16.5	3.8	22.4	3.6	27.4	3.5	30.9	24
26														3.4	12.6	3.3	19.8	3.1	25.2	3.1	28.9	26
28														3.0	4.5	2.9	16.4	2.7	22.9	2.6	26.8	28
30																2.5	11.5	2.3	19.8	2.3	24.1	30
32																		2.0	15.8	2.0	19.0	32
34																		1.7	10.0	1.7	17.1	34
36																				1.5	12.0	36

Q - грузоподъёмность (в тоннах); Q* - стрела повернута назад (0°); H - высота подъёма крюка (в метрах)